

What I claim is:

1. A flush toilet for dogs having various physical sizes, comprising
a generally flat platform adapted for a dog to stand and deposit excrements thereon,
two upstanding opposite high side wall portions extending from a middle portion to a
5 rear end of said platform, two low baffle walls formed at a front edge of said high side wall
portions and extending perpendicular to said high side walls portions, said baffle walls being
adapted to prevent urine ejected by a male dog against said high side wall portions from
splashing out of said toilet,

a restraint frame adjustably mounted on said side wall portions and adapted for retaining
10 the dog within said toilet, said restraint frame being adjustable to a selected position for
accommodating a dog of any physical size to stand within said toilet,

a water duct located within an upper edge portion of said side wall portions,

a plurality of water openings formed around said edge portion of said side wall portions
and operative for injecting flush water delivered from said water duct for flushing and cleaning
15 said platform,

a drain opening located at a middle front position of said platform and adapted to dispose
excrements flushed from said platform by said flush water.

2. A flush toilet according to Claim 1 including a grid pattern and a pictorial depiction of an
outdoor scenery provided an inner surface of said high side wall portions.

20 3. A flush toilet according to Claim 2 wherein said restraint frame includes two vertical
posts having a U-shaped upper end and an inverted U-shaped bracket located at a lower end
therein, adjustable mounting means provided at said bracket for mounting said posts to said side

wall, a cross bar having one end hingedly mounted to the U-shaped upper end of one of said posts and having a free end pivotally engageable with the U-shaped upper end of the other one of said posts to located in a transverse position above said platform, and said posts being adjustable to locate at a selected position of said side wall for accommodating said pet of any physical size standing within said platform.

4. A flush toilet according to Claim 3 including a mounting ring provided on said cross bar.

5. A flush toilet according to Claim 4 wherein said toilet is made selectively of a porcelain, metal, and plastic material.

6. A flush toilet according to Claim 5 including an elongated channel formed at a center of said platform, said channel extending from said drain opening to a front portion of said platform.

7. A flush toilet according to Claim 6 including a sloping ramp provided at said front end and at said rear end of said platform.